



(highlight:at the glance) CEV Champions League: Volleyball Women (68m, perimeter system & operation)

LED TECHNOLOGY AT CEV CHAMPIONS LEAGUE LEVEL!

TSCHILIN 10AIRS

MODUL	Application	indoor fix- or mobile-installation	screen, score-, fascia-bord, perimeter system	
	Resolution	10mm, asymmetric pixel pitch	LED Type: ReeStar RS-2727 MWAR high brightness, customized selected batch	
	Size & Material	400 x 450 mm (W x H) 4,8kg	aluminium-alloy, die casting, lightweight	
	Brightness	2200 nits	after calibration	
	View Angle	170° with high flatness (for wide viewing angle)	result in a readable content from the baseline football field camera	
	Body Structure	close- & fanless-system dust- & water-protection IP67 front / back	design for longlife with selected components, optimized heat absorption, fast lock system	
	Technology	modular structure with dual power supply for redundancy, fully data-redundancy	together with selected components an ultrafast image build-up without ghost shadow effect	
	Gray Scale	16 bit / PWM driver (SUM 2035)	hardware-based technology for natural color, high contrast, from 1% to 100% luminosity	
	Scan Rate	1/4		
	Sport Photographer	1 : 1600 / sec, shutter speeds	no missing image information (black lines)	
	Broadcast, TV	50Hz Signal Frequenz / 3850 Hz refresh rate 60Hz Signal Frequenz / 3860 Hz refresh rate	50Hz national broadcast, 60Hz international broadcast flicker free up to hyper slow-motion cam's	
	Front Mask	LSS laminated front rubber mask EN 13823 EN ISO 1716 (SMOGRA, FIGRA, THR, TSP)	flatness guarantee up to 80 ° C, UV-protected	
	PANEL	Service	front & back maintenance	hot plug maintenance
Alignment		perimeter, horizontal, 90° straight screen: horizontal, vertical	perimeter: mounting feed system, soft top cover screen & fascia: wall mounting system	
Frame		panel size 1600 x 900mm (16:9) (perimeter with feet & top cover = 950mm)	aluminium extruded process 48kg/m ² perimeter panel weight complete	
Gates (Perimeter)	combined swing access- & exit-gate (optional)	both way open: to the field, from the field away		
SYSTEM	LED Controller	full redundant system with UPS	HDMI input, Fiber Channel output (1GB)	
	PlayOut System	SLAM.SYSTEMS modular and redundant PlayOut System, control, administration playback (optional)	graphical-interface, playlist admin, virtual add, fan engagement, scoreboard, brightness control with sun shader adjustment	
	Handling	fast system setup-ready to play (40 m = 2 person, 4h)	2 technician/stage hands	
	Virtual Advertising	virtual advertising technology on ready	updateable System for virtual advertising technology	
	Power Consumption green efficiency	51.3W/m ²	stand:by mode in watt by 225V/50Hz	
		155W/m ² 229.5W/m ²	average power consumption: based on 88m ² LED-Perimeter with floodlights and a mix of animated/static content during the game maximum power consumption by full white and full brightness	
	Lab	CE, RoHS, EMC class A (high-level)	current inrush limiting for system power soft-start	
Compliance	Swiss warranty	In-house development & production for a long lifetime with guaranteed spare parts supply through selected components, inexpensive maintenance , 20 years experience in LED technology		



modular cabinet 800x900mm, feet, top cover, fast installation



aluminium di-cast modules: robust – reliable – durable



technical changes reserved – ©2023